

Siding Mounting Block

Mounting block with built in electrical box for smooth vertical mounting of light fixtures on all siding types. Paintable. UV rated plastic for long outdoor life.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	SIDING TYPE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	DIM D
8141F	10761	All Types	10	10	6.652	6.652	4.125" Diameter x 1/2" Deep	1.126

  **MADE IN USA.**
E170558 LR49636

Add suffix "GC" to Catalog # when ordering in Canada to include grounding clip, for example 8141FGC.

FEATURES AND BENEFITS

- One piece design
- Textured, paintable surface
- NM cable connector included
- Installs before or after siding is installed. Remove break away flanges for installation on previously sided structures.

INSTALLATION INSTRUCTIONS

BEFORE siding is up:

- 1) Remove knockout from 8141F. Insert cable connector. Pull NM cable through connector.
- 2) Attach block to substrate with (2) screws mounted diagonally.
- 3) Install fixture according to manufacturer's instructions.

AFTER siding is up:

- 1) Cut hole in siding.
- 2) Break flanges off the back of the 8141F. Remove knockout. Insert cable connector in KO, then pull NM cable through connector.
- 3) Attach mounting block to substrate with (2) screws.
- 4) Install fixture according to manufacturer's instructions.

