Heavy duty, Non-Metallic **Quick**LATCH™

more on

Installed Strut Clip • For RIGID and EMT





1 Insert QuickLatch into strut. The strut clip is already attached so you save time.



2 Twist QuickLatch to seat clip in strut.



3 Tighten screw for secure installation on strut.



4 Push conduit into QuickLatch to snap in place.



5 Secure installation of conduit to strut



Easy screwdriver removal















QUICKLATCH™ PIPE HANGER

Catalog Number	UPC/DEI/NAED Mfg. #018997	Rigid, IMC, PVC Size	EMT Size	Std Pkg
NM3100	54027		1/2"	100
NM3105	54028	1/2"		100
NM3110	54029		3/4"	100
NM3115	54030	3/4"		100
NM3120	54031		1"	100
NM3125	54032	1″		100

NM3100 series 0325/15M © 2020 Arlington Industries. Inc.

Arlington's heavy duty NM3100 series

QuickLatch™ with installed strut clip



One-piece QuickLatch saves time, about 20 seconds per installation... over 33¢ each at \$60.00 per hour labor rate.

Fast and easy to install. Insert the hanger into the strut, twist to lock the pre-installed clip in place then tighten screw to secure QuickLatch to strut.

Push RIGID or EMT into the hanger to lock it in place.

- UV rated, corrosion resistant for outdoor use
- Stainless steel screw
- Mounts vertically or horizontally
- Screwdriver removal, reusable
- Listed for use in environmental air handling spaces per 2020 NEC, article 300.22(c)

See reverse for even more QuickLatch products!







Arlington®

1 Stauffer Industrial Park Scranton, PA 18517 800/233.4717 • Fax 570/562.0646 www.aifittings.com

UV Rated, Non-Metallic **Quick**LATCH™

Works just like a Pipe Hanger • Easy to Install



Mount to surface with a screw.



Press down on pipe to lock it firmly in place.



Removable Use screwdriver

Fast and easy to install, one-piece, non-metallic QuickLATCH™ mounts to walls, metal strut and studs, and threaded rod up to 1/4-20...works with Arlington's Strut Clip™ too. Strut Clip holds pipe hangers securely on strut.

It fits 1/2" to 4" EMT, RIGID, IMC and PVC. The larger 2-1/2" to 4" sizes have an extra opening for the optional securing of tie wire or cable tie.

- Corrosion resistant
- · Horizontal or vertical mounting
- · Integral slot keeps nut from spinning



2-1/2" to 4"

Press pipe into QuickLatch, up to the first notch to lock it in place. Then squeeze tabs together for a super-secure hold.



Catalog Number	UPC/DEI/NAED Mfg. #018997	Rigid, IMC, PVC Size	EMT Size	LT Size	Flex Size	ENT Size	Copper Tubing	Copper Pipe	Std Pkg
NM1900	54514			5/16''			1/2"		100
NM2000	54515		1/2''	3/8"				3/8"	100
NM2005	54525	1/2"		1/2"	1/2''	1/2"		1/2"	100
NM2010	54516		3/4"				3/4"		100
NM2015	54526	3/4"		3/4"	3/4"	3/4"		3/4''	100
NM2020	54517		1"				1"		100
NM2025	54518	1"		1"	1"	1"		1"	100
NM2030	54528		1-1/4''				1-1/4''		100
NM2040	54519	1-1/4''	1-1/2''				1-1/2"	1-1/4''	100
NM2045	54544	1-1/2''		1-1/2''	1-1/2''			1-1/2"	100
NM2150	54547						2"		50
NM2050	54520	2"	2"	2"	2"		2"		50
NM2060	54521	2-1/2''	2-1/2''	2-1/2''	2-1/2''				50
NM2070	54522	3"	3"	3"	3"				25
NM2080	54523	3-1/2"	3-1/2"	3-1/2"	3-1/2"				25
NM2090	54524	4"	4"	4''	4"				10

Catalog	UPC/DEI/NAED	Description	Unit/Std
Number	Mfg. #018997	STRUT CLIP™	Pkg
NM1000	54615 Hol	UV rated, non-metallic clip ds pipe hangers and/or conduit secure on stru Includes 1/4"-20 screw (installed)	100 it



1 Stauffer Industrial Park Scranton, PA 18517

www.aifittings.com

800/233.4717 • Fax 570/562.0646

NM1000 STRUT CLIP Strut Conduit Support







Distributed by

