




Color: ■ gray

Application Examples

- Bathroom installation (DIN VDE 0100-701)
- Washing facilities/irrigation systems
- Farms and garden centers (DIN VDE 0100-0705)
- Swimming pool areas (DIN VDE 0100-702)
- Parking lot lighting
- Charging stations and lighting systems in ports

Note on Packaging Unit (PU) and Subpackaging Unit (SPU):

If you order a full PU, you will receive our eco-friendly, sustainable cardboard blisters packed in a shelf-ready box.
If you order a quantity smaller than a full PU, you will receive the eco-friendly, sustainable cardboard blisters without a shelf-ready box.

Please refer to the system description for the splicing connectors that can be used.

Your Benefits:

- Easy, fast and safe to use
- Can be used immediately and accessed again later
- Silicon-free
- Label-free
- Suitable for indefinite storage
- The complete system, which consists of gelboxes and WAGO splicing connectors, has been VDE-tested and IPX8-certified.

Connection data		
Connection 1		
Actuation type	Locking system	
Physical data		
Width	57 mm / 2.244 inches	
Height	21.3 mm / 0.839 inches	
Depth	40.1 mm / 1.579 inches	



Mechanical data		
Design	Size 3	
Mounting type	Flying leads	
Protection type	IPX8	
Suitable	for 6 mm² splicing connectors	

Material data		
Note (material data)	Information on material specifications can be found here	
Color	gray	
Housing material	Polypropylene	
Fire load	0 MJ	
Weight	35.4 g	

Environmental requirements		
Ambient temperature (operation)	-55 ... +85 °C	
Ambient temperature (storage)	0 ... +40 °C	

Commercial data		
PU (SPU)	24 (2) pcs	
Packaging type	Box	
Country of origin	IT	
GTIN	4055144097306	
Customs tariff number	85389099990	

Product classification		
UNSPSC	39121722	

Environmental Product Compliance		
RoHS Compliance Status	Compliant,No Exemption	

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
VDE VDE Prüf- und Zertifizierungsinstitut	EN 60669	400051938

Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-
UK-Declaration of Conformity WAGO GmbH & Co. KG	-	-



Downloads		
Environmental Product Compliance		
Compliance Search		
Environmental Product Compliance 207-1433		↓

Documentation					
System Description			Additional Information		
System Description 207 Series Gel boxes	pdf	1156.45 KB	Certificate	pdf	2308.76 KB
		↓			↓
System Description 207 Series Gel boxes	pdf	1191.37 KB	DLG Test Report 7438	pdf	1455.46 KB
		↓			↓

Bid Text		
207-1433	xml	3.58 KB
		↓
207-1433	docx	20.42 KB
		↓

CAD/CAE-Data	
CAD data	
2D/3D Models 207-1433	↓

Installation Notes			
Installation			
			
Open the Gelbox at the side latches.	Place the wired connector in the Gelbox.	Place the wired connector in the Gelbox.	Close the Gelbox.
			
Close latch securely.	Re-accessible: • Open the Gelbox. • Remove the gel. • Rewire with new components.		



Lift the flap and pull the cover perforation forward.



Press in the perforation on the sides.



Tear off the cover from the perforation.



As a counter display: Bend the rear flap at the fold, straighten it and fix it in the cardboard cut-out



If the flap is not required, tear off from the perforation.