

## Data Sheet | Item Number: 221-483


Splicing connector with levers; for all conductor types; for Ex e applications; max. 4 mm<sup>2</sup>; 3-conductor; transparent housing; Operating temperature (max.): 105 °C; 4,00 mm<sup>2</sup>; transparent

<https://www.wago.com/221-483>



Color: ☐ transparent





Dimensions in mm

Splicing connector with levers, 221 Series, transparent

Splicing connector with levers (item number 221-483) simplifies electrical installations. Whether for intercom system wiring or connecting electrical ovens, WAGO's 221 Series splicing connector allows you to quickly and safely connect different conductor types. Its compact design offers an efficient solution that simplifies your work. Conductors can only be connected to splicing connector with levers if their strip length is 11 mm. This product features conductor terminals and utilizes CAGE CLAMP®. Our renowned universal connection known as CAGE CLAMP® is the industry standard for connection technology and electrical interconnections. Dimensions: 18.8 x 8.4 x 18.6 mm (width x height x depth). Depending on the type of conductor, splicing connector with levers is ideal for conductor cross sections ranging from 0.2 mm² to 4 mm².

WAGO's 221 Series Splicing Connector with levers impresses with its innovative design for different conductor cross-sections. That's why WAGO's lever-equipped splicing connector holds a unique trademark within electrical interconnection technology. The flat levers, which fit seamlessly into the 221's base, act like a cast when closed and can be positioned neatly in any housing without disturbing edges. Due to the wide design of each lever, they can all be operated perfectly without tools for convenient conductor terminations. The transparent housing displays robust technology and enables immediate visual inspection for the correct contact of solid, stranded and fine-stranded conductors. Resembling piano keys, the levers' design perfectly combines the functional and aesthetic connection technology "Made by WAGO." This product is designed for specific Ex applications (please refer to the product datasheet).

Notes	
General safety instructions	<div><b>NOTICE: Observe installation and safety instructions!</b></div> <div><ul style="list-style-type: none"><li>• <b>Only to be used by electricians!</b></li><li>• Do not work under voltage/load!</li><li>• Use only for proper use!</li><li>• Observe national regulations/standards/guidelines!</li><li>• Observe technical specifications for the products!</li><li>• Observe the number of permissible potentials!</li><li>• Do not use damaged/dirty components!</li><li>• Observe conductor types, cross-sections and strip lengths!</li><li>• Insert conductor until it hits the product's backstop!</li><li>• Use original accessories!</li></ul></div> <div><b>To be sold only with installation instructions!</b></div>
Safety Information	The permissible operating voltage of the connector with carrier (440 V or 275 V) depends on the mounting type.
Safety information 2	<div>Only approved in conjunction with a mounting carrier (221-501). Other carriers are possible, see certificate/file. The connectors must be installed in an enclosure meeting the requirements of a recognized protection type per EN 60079-0, GB/T 3836.1 Section 1 or EN 60079-31, GB/T 3836.31. When installing the connectors in an enclosure of protection type "e" (increased safety per EN 60079-7, GB/T 3836.3), the clearances and creepage distances of Table 2 for this standard must be observed. See point 1 for the use of accessories. The connectors can be used both in Group II and Group I, as the standard requirements are identical in this case.</div> <div>The use of these components requires a new assessment by a notified certification agency.</div>



Electrical data			
Approvals per		UL 60079	
Use group	B	C	D
Rated voltage	-	440 V	-
Rated current	-	20 A	-
Ex information		ATEX: PTB 18 ATEX 1019 U / IECEx: PTB 18.0045U (Ex eb IIC Gb)	
Rated voltage EN (Ex e II)		440 V	
Rated current (Ex e II)		32 A	

Connection data	
Clamping units	3
Total number of potentials	1
Connection 1	
Connection technology	CAGE CLAMP®
Actuation type	Lever
Connectable conductor materials	Copper
Nominal cross-section	4 mm² / 12 AWG
Solid conductor	0.2 ... 4 mm² / 24 ... 12 AWG
Stranded conductor	0.2 ... 4 mm² / 24 ... 12 AWG
Fine-stranded conductor	0.14 ... 4 mm² / 24 ... 12 AWG
Strip length	11 mm / 0.43 inches
Wiring direction	Side-entry wiring

Physical data	
Width	18.8 mm / 0.74 inches
Height	8.4 mm / 0.327 inches
Depth	18.6 mm / 0.732 inches

Material data	
Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	transparent
Material group	Illa
Insulation material (main housing)	Polycarbonate (PC)
Flammability class per UL94	V2
Fire load	0.064 MJ
Actuator color	light gray
Weight	2.7 g

Environmental requirements	
Ambient temperature (storage)	-40 ... +60 °C
Continuous operating temperature	-55 ... +105 °C




Commercial data	
PU (SPU)	500 (50) pcs
Packaging type	Box
Country of origin	DE
GTIN	4055143837347
Customs tariff number	85369010000




Product classification	
UNSPSC	39121409

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Approvals / Certificates

General approvals			Declarations of conformity and manufacturer's declarations		
<div></div>					
Approval	Standard	Certificate Name	Approval	Standard	Certificate Name
CCA DEKRA Certification B.V.	EN 60998	NTR NL-7990	ATEX-Attestation of Con- formity WAGO GmbH & Co. KG	-	-
cULus_Listed_667F Underwriters Laboratories Inc.	UL 486C	E69654	EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
ENEC 05 DEKRA Certification B.V.	EN 60669,EN 60998	71-127529	UK-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-

Approvals for marine applications			Approvals for hazardous areas		
			     		
Approval	Standard	Certificate Name	Approval	Standard	Certificate Name
LR Lloyds Register	EN 60998	LR22207029TA	AEx Underwriters Laboratories Inc.	UL 60079	E185892 (AEx eb IIC resp. Ex eb IIC)
			ATEX Physikalisch Technische Bundesanstalt	EN IEC 60079-0	PTB 18 ATEX 1019 U (II 2 G Ex eb IIC Gb, I M 2 Ex eb I Mb)
			CCC CNEX	GB/T 3836.3	2020312313000184 (Ex eb IIC Gb, Ex eb I Mb)
			IECEX Physikalisch Technische Bundesanstalt	IEC 60079-0	IECEX PTB 18.0045U (Ex eb IIC Gb, Ex eb I Mb)
			INMETRO TÜV Rheinland do Brasil Ltda.	IEC 60079	TÜV 19.1781 U

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 221-483	

Documentation			
System Description		Bid Text	
System Description 221-482, 221-483, 221-485	pdf 1151.51 KB ↓	221-483 21.05.2019	docx 16.02 KB ↓
		221-483 21.05.2019	xml 4.09 KB ↓
		ausschreiben.de 221-483	↓

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 221-483 ↓	EPLAN Data Portal 221-483 ↓
	ZUKEN Portal 221-483 ↓

1 Compatible Products
1.1 Optional Accessories
1.1.1 Mounting adapter
1.1.1.1 Mounting accessories



**Item No.: 221-500/000-006**  
Mounting carrier; 221 Series - 4 mm²; for  
DIN-35 rail mounting/screw mounting;  
blue

**Item No.: 221-501**  
Mounting carrier; for Ex applications; 221  
Series - 4 mm²; for DIN-35 rail mounting/  
screw mounting; light gray

Installation Notes
Conductor termination



Strip conductor to 11 mm (0.43 inch).

Then, lower the lever to close the clamp.

Termination: Lift the lever to open the  
clamping unit and insert a stripped  
conductor.

Installation			
Inserting a connector into the mounting carrier.	Removing a connector from the mounting carrier.	Removing a conductor.	<b>Mounting type (440 V)</b> Using spacers between the connectors.

## Installation

**Mounting type (440 V)**


Vertical mounting on DIN-35 rail

**Mounting type (440 V)**

Horizontal screw mounting on a flat surface

**Mounting type (440 V)**

Mounting the carrier via non-conductive screws.

**Mounting type (275 V)**

No spacers are used between the connectors.

**Mounting type (275 V)**

Mounting the carrier using conductive screws.

## Testing



Easily test inserted connectors in the carrier –  
however they are mounted.