


Color: white



Dimensions in mm

Physical data	
Width	23.7 mm / 0.933 inches
Height from the surface	16.9 mm / 0.665 inches
Depth	52.8 mm / 2.079 inches

Mechanical data	
Mounting type	Screw mount
Suitable	for 3-wire connectors (4 mm²)

Material data	
Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	white
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0 MJ
Weight	3.6 g

Commercial data	
PU (SPU)	50 (10) pcs
Packaging type	Box
Country of origin	CN
GTIN	4055143640794
Customs tariff number	39269097900



Product classification		
UNSPSC		39121409

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 221-503	<a href="#">↓</a>

Documentation				
Bid Text				
221-503	19.02.2019	xml 2.70 KB		<a href="#">↓</a>
221-503	04.01.2018	doc 23.50 KB		<a href="#">↓</a>

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 221-503	EPLAN Data Portal 221-503
	ZUKEN Portal 221-503

1 Compatible Products
1.1 Optional Accessories
1.1.1 Marking
1.1.1.1 Marking strip



Item No.: 210-833  
Marking strips; 25 m on roll; 6 mm wide;  
plain; Self-adhesive; white

Installation Notes



Inserting a connector into the mounting carrier.

Removing a connector from the mounting carrier.

Conductor termination



Inserting a conductor.



Horizontal screw mounting



Vertical screw mounting



Horizontal mounting via snap-in foot



Vertical mounting via snap-in foot

Strain relief



Use a cable tie to secure the conductors to the strain relief plate.



The strain relief plate can be removed.

Testing



Testing a connector mounted on the carrier via test slot.

## Application



Connecting a light to the mains.

## Marking



Labeling the mounting carrier.