

## Offers excellent dexterity and comfortable hand protection with an ergonomic design

- **Heightened tactility and comfort:** These soft, thin nitrile gloves reliably protect while offering exceptional fit and tactility for jobs requiring fine motor control
- **ERGOFORM™ Technology:** Proven to reduce the amount of muscle effort wearers exert while performing repetitive tasks when compared to similar disposable nitrile gloves\*
- **Food handling compliance:** Suitable for a wide variety of food handling scenarios
- **Smart-packed:** Smartly packed with 300 gloves per dispenser box\*\*
- **Available in half sizes:** Available in XS/S, S/M, M/L in addition to normal sizes to ensure a perfect fit



\*based on lab tests conducted by US Ergo and commissioned by Ansell

\*\*size XL is packed with 250 gloves per dispenser box

### Industries

- Food Processing
- Life Sciences
- Healthcare
- Agriculture
- Automotive
- Utilities
- Warehousing

### Recommended For

- Protection from Type I latex allergy in HCW's or patients
- Enhanced tactile sensitivity and dexterity, especially for delicate procedures
- Brief, low-risk examination procedures
- Extra comfort during long, sustained procedures
- Plant disinfection and sanitization
- All food processing, applications that have food contact
- Assembly of parts
- Sample taking and processing
- Extra comfort during long, sustained procedures

TECHNICAL DATA SHEET

|                        | Product Information                                                                                                                                  |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material               | Nitrile                                                                                                                                              |
| External Glove Surface | Textured Fingers                                                                                                                                     |
| Audit Standards        | EN ISO 13485:2012                                                                                                                                    |
| Product Certification  | Korean Standard                                                                                                                                      |
| Packaging Overview     | 300 gloves per dispenser<br>10 dispensers per case<br>3000 gloves per case<br>*250 gloves per dispenser (Size XL)<br>*2500 gloves per case (Size XL) |
| Storage Instructions   | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.                                             |
| Country Of Origin      | China                                                                                                                                                |
| Product Segmentation   | High Touch                                                                                                                                           |
| Antistatic             | No                                                                                                                                                   |
| Silicone Free          | No                                                                                                                                                   |

PHYSICAL PROPERTIES

|                                         | Typical Values |             | Testing Method      |
|-----------------------------------------|----------------|-------------|---------------------|
| Length (mm/inches)                      | 230 / 9.1      |             | ASTM D3767,EN 420   |
| Freedom from Holes (Inspection level I) | 1.5 AQL        |             | ASTM D5151,EN 455-1 |
| Palm Thickness (mm/mils)                | 0.06 / 2.4     |             | ASTM D3767,EN 420   |
| Finger Thickness (mm/mils)              | 0.10 / 3.9     |             | ASTM D3767,EN 420   |
|                                         | BEFORE AGING   | AFTER AGING |                     |
| Ultimate Tensile Strength (MPa)         | 23             | ≥ 14        | ASTM D412 & D573    |
| Elongation at Break (%)                 | ≥ 500          | ≥ 400       | ASTM D412           |
| Force at break (N)                      | ≥ 3            | ≥ 3         |                     |

ORDERING INFORMATION

| Size         | XS (5.5 - 6) | XS-S (5.5- 7.0) | S (6.5 - 7) | S/M (7.5) | M (7.5 - 8) | M-L (7.5- 9.0) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|--------------|-----------------|-------------|-----------|-------------|----------------|-------------|---------------|
| Product Code | UF-524-XS    | UF-524-XSS      | UF-524-S    | UF-524-SM | UF-524-M    | UF-524-ML      | UF-524-L    | UF-524-XL     |

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

**Europe, Middle East & Africa Region**  
Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01  
  
**Asia Pacific Region**  
MY: +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

**North America Region**  
Ansell Healthcare Products LLC  
T: +1 800 800 0444  
F: +1 800 800 0445  
  
**Latin America & Caribbean Region**  
BR: +55 (11) 3356-3100  
latam.medical@ansell.com  
MX: +52 442 296 2050  
latam.medical@ansell.com  
CO: +57 1 288 3247  
latam.medical@ansell.com

**Australia**  
Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578  
  
**Russia**  
Ansell PYC  
Ten. +7 495 258 13 16

Technology



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

